

Crop shredder



Спецификации

Тип	CS Robust 310
Марка	Bio Bull
Код	25092S
Engine	John Deere 310 HP diesel engine
Control	Remote control
Infeed correction	Included
Tank capacity	180 liter
Cutting unit	800 mm
Capacity maximum	Up to 15000 m² per hour (depending on product)

25092S-V23060601-RU

**Renewed
Quality
Machines and
Materials**



Hortimat - Vlotlaan 192, 2681
TV Monster, The Netherlands

T +31(0)174 38 71 10 E info@hortimat.com
W www.hortimat.nl

Metal detection	Optionally available
Wheels	VTS caterpillar track with 5 support rolls
Weight	7500 kg
Length	8350 mm
Width	2180 mm
Height	2200 mm

The Bio Bull crop shredder 310 Robust is a solid, powerful crop shredder.

The Bio Bull is robustly built with the philosophy of a maintenance-friendly machine with a guaranteed long service life

The Bio Bull crop shredder 310 Robust has the following two major advantages over its competitors:

-The price / quality of the Bio Bull is at a high level

-The Bio Bull 310 is equipped with a more powerful engine than comparable competitors (up to more than 100 hp stronger)

The Bio Bull is equipped with a John Deere diesel engine which can optionally be supplied with a Stage 5 engine.

This engine ensures that you are built in accordance with all (required) laws, environmental and regulations. John Deere offers worldwide service!

All conveyor belts on the machine can be adjusted separately for speed.

This makes the machine perfect for any situation / crop.

Input table:

The input table can be input on both sides.

The input table is extra secured by means of hydraulic shields on both sides. These automatically protects the roll-up unit and guarantees a safe input situation.

These also reduces physical strain.

Cage:

The Claas-cage is 800 mm wide and is equipped with a knife sharpener. These cages are robustly built and ensure a maintenance-friendly, long service life. (Spare) parts of these cages are available worldwide.

The output of the cage is by means of a conveyor belt. This conveyor belt is hydraulically adjustable in height and empties the shredded crop onto the buffer belt.

Buffer:

The buffer belt is provided with a elevator belt. This buffer has a width of 1,600 mm and can hold a maximum of 4 to 5 m3. This buffer allows the shredding process to continue while the tipping containers are being exchanged or emptied. Because the shredder empties its shredded crop onto the buffer, no empty tipping containers is required to be able to keep on shredding.

The buffer can be operated by means of a separate remote control. As a result, the forklift driver keeps a safe distance from the machine and the machine operator can focus on shredding and its personnel.

Hortimat работы по модификации под заказ

Hortimat может модифицировать предложенное оорудование под нужды заказчика. Опционально мы можем конструктивно настроить оорудование или установить новую операционную систему. Мы так же можем поставить индивидуальные решения в форме логистических конвейерных ленточных систем, и мы мысли вместе с заказчиком для лучшего результата в модификации под его запросы.

Почему Hortimat

- + Adapting / modifying of used machines to desired specifications of the customer
- + Applying of new 2023 operating systems on used machines
- + New Hortimat range of products
- + Service and warranty by own technical specialists
- + Solid revision; guarantees a long lifetime
- + Individual advice about logistics matters, such as: grading machines, processing areas